



LANCER BLADE DDR5 MEMORY

## SLEEK EFFICIENCY, COMPACT POWER

### LANCER BLADE DDR5 MEMORY

The LANCER BLADE adopts a low-profile heatsink design, removing height consideration from heatsink assembly, and making the product suitable for installation in small chassis. The heatsink is decorated in simple geometric lines, which are a versatile look when paired with various chassis types. The LANCER BLADE has undergone strict component selection and screening procedures, and passed reliability and compatibility tests. It is strong and durable, offering the highest quality! The LANCER BLADE supports AMD EXPO and is compatible with the latest AMD platform. It also supports Intel XMP 3.0 overclocking, providing players with excellent overclocking performance.

#### Features

- Compact Low-Profile Heatsink Design
- PMIC for power supply stability
- On-die ECC error correction
- High-quality materials for stable overclocking
- Works with the Latest AMD Platforms
- Supports Intel® XMP 3.0 and AMD EXPO for easy overclocking

#### Specifications

- Heatsink Color: Black/White
- Speed: DDR5 5600/6000/6400 MT/s
- CAS Latencies: 46-45-45/30-40-40 & 48-48-48 & 34-38-38 & 36-38-38/32-39-39
- Module size: 8GB/16GB/32GB
- Packaging: 8GB/16GB/32GB (Single/Dual)
- Operating temperature: 0°C to 85°C
- Storage temperature: -20°C to 65°C
- Operating voltage: 1.1V-1.4V
- Compatibility: DDR5 4800 CL40-39-39 at 1.1V
- Dimensions(LxWxH): 133.35 x 33.8 x 7.8mm
- Weight: 32.9g / 36.2g
- Warranty: Limited Lifetime Warranty



## Model Number / EAN Code

### Black

Package	Speed/Capacity		Latency	Model Number	EAN Code
Single Tray	5600MT/s	8GB	CL 46-45-45	AX5U5600C468G-SLABBK	4711085947987
	5600MT/s	16GB	CL 46-45-45	AX5U5600C4616G-SLABBK	4711085945440
	5600MT/s	32GB	CL 46-45-45	AX5U5600C4632G-SLABBK	4711085948021
	6000MT/s	16GB	CL 30-40-40	AX5U6000C3016G-SLABBK	4711085944535
	6000MT/s	16GB	CL 34-38-38	AX5U6000C3416G-SLABBK	4711658150134
	6000MT/s	16GB	CL 48-48-48	AX5U6000C4816G-SLABBK	4711085948359
	6000MT/s	16GB	CL 36-38-38	AX5U6000C3616G-SLABBK	4711658152275
	6000MT/s	32GB	CL 30-40-40	AX5U6000C3032G-SLABBK	4711085944566
	6000MT/s	32GB	CL 34-38-38	AX5U6000C3432G-SLABBK	4711658150431
	6400MT/s	16GB	CL 32-39-39	AX5U6400C3216G-SLABBK	4711085944603
	6400MT/s	32GB	CL 32-39-39	AX5U6400C3232G-SLABBK	4711085944641
Dual Tray	5600MT/s	8GB	CL 46-45-45	AX5U5600C468G-DTLABBK	4711085947994
	5600MT/s	16GB	CL 46-45-45	AX5U5600C4616G-DTLABBK	4711085945457
	5600MT/s	32GB	CL 46-45-45	AX5U5600C4632G-DTLABBK	4711085948038
	6000MT/s	16GB	CL 30-40-40	AX5U6000C3016G-DTLABBK	4711085944382
	6000MT/s	16GB	CL 34-38-38	AX5U6000C3416G-DTLABBK	4711658150141
	6000MT/s	16GB	CL 48-48-48	AX5U6000C4816G-DTLABBK	4711085948366
	6000MT/s	16GB	CL 36-38-38	AX5U6000C3616G-DTLABBK	4711658152282
	6000MT/s	32GB	CL 30-40-40	AX5U6000C3032G-DTLABBK	4711085944573
	6000MT/s	32GB	CL 34-38-38	AX5U6000C3432G-DTLABBK	4711658150448
	6400MT/s	16GB	CL 32-39-39	AX5U6400C3216G-DTLABBK	4711085944610
	6400MT/s	32GB	CL 32-39-39	AX5U6400C3232G-DTLABBK	4711085944658



## White

Package	Speed/Capacity		Latency	Model Number	EAN Code
Single Tray	5600MT/s	8GB	CL 46-45-45	AX5U5600C468G-SLABWH	4711085949837
	5600MT/s	16GB	CL 46-45-45	AX5U5600C4616G-SLABWH	4711085945426
	5600MT/s	32GB	CL 46-45-45	AX5U5600C4632G-SLABWH	4711085948007
	6000MT/s	16GB	CL 30-40-40	AX5U6000C3016G-SLABWH	4711085944542
	6000MT/s	16GB	CL 34-38-38	AX5U6000C3416G-SLABWH	4711658150158
	6000MT/s	16GB	CL 48-48-48	AX5U6000C4816G-SLABWH	4711085948335
	6000MT/s	16GB	CL 36-38-38	AX5U6000C3616G-SLABWH	4711658152251
	6000MT/s	32GB	CL 30-40-40	AX5U6000C3032G-SLABWH	4711085944580
	6000MT/s	32GB	CL 34-38-38	AX5U6000C3432G-SLABWH	4711658150455
	6400MT/s	16GB	CL 32-39-39	AX5U6400C3216G-SLABWH	4711085944627
	6400MT/s	32GB	CL 32-39-39	AX5U6400C3232G-SLABWH	4711085944665
	Dual Tray	5600MT/s	8GB	CL 46-45-45	AX5U5600C468G-DTLABWH
5600MT/s		16GB	CL 46-45-45	AX5U5600C4616G-DTLABWH	4711085945433
5600MT/s		32GB	CL 46-45-45	AX5U5600C4632G-DTLABWH	4711085948014
6000MT/s		16GB	CL 30-40-40	AX5U6000C3016G-DTLABWH	4711085944559
6000MT/s		16GB	CL 34-38-38	AX5U6000C3416G-DTLABWH	4711658150165
6000MT/s		16GB	CL 48-48-48	AX5U6000C4816G-DTLABWH	4711085948342
6000MT/s		16GB	CL 36-38-38	AX5U6000C3616G-DTLABWH	4711658152268
6000MT/s		32GB	CL 30-40-40	AX5U6000C3032G-DTLABWH	4711085944597
6000MT/s		32GB	CL 34-38-38	AX5U6000C3432G-DTLABWH	4711658150462
6400MT/s		16GB	CL 32-39-39	AX5U6400C3216G-DTLABWH	4711085944634
6400MT/s		32GB	CL 32-39-39	AX5U6400C3232G-DTLABWH	4711085944672

## Package Information

### Single Tray

Model	Bulk+HS Weight (g)	Retail Weight (g)	Single Tray Dimensions (LxWxH/mm)	Carton Dimensions (LxWxH/mm)	Cuft	Qty per carton	Carton N.W. (g)	Carton G.W. (g)
DDR5 U-DIMM 8G (1-rank)	32.35	51.09	170 x 70 x 12.2	340 x 300 x 212	0.76	120	6,131	6,867
DDR5 U-DIMM 16G (1-rank)	32.9	51.64	170 x 70 x 12.2	340 x 300 x 212	0.76	120	6,197	6,933
DDR5 U-DIMM 32G (2-rank)	36.2	55	170 x 70 x 12.2	340 x 300 x 212	0.76	120	6,600	7,336

### Dual Tray

Model	Bulk+HS Weight (g)	Retail Weight (g)	Dual Tray Dimensions (LxWxH/mm)	Carton Dimensions (LxWxH/mm)	Cuft	Qty per carton (PAR)	Carton N.W. (g)	Carton G.W. (g)
DDR5 U-DIMM 8G (1-rank)	32.35	105.75	170 x 141 x 12.2	340 x 300 x 212	0.76	60	6,345	7,081
DDR5 U-DIMM 16G (1-rank)	32.9	106.3	170 x 141 x 12.2	340 x 300 x 212	0.76	60	6,380	7,116
DDR5 U-DIMM 32G (2-rank)	36.2	113	170 x 141 x 12.2	340 x 300 x 212	0.76	60	6,780	7,516



Single Tray Package

Dual Tray Package